

Pushover Silage Pusher (Silage & Feed Mover)

OVERVIEW

The Browns Pushover Silage Pusher makes it easy to keep feed close to the barrier and within reach of your livestock. Its adjustable width suits a range of passage sizes, and the angled tyres move silage smoothly without leaving gaps. Built for everyday farm use, it attaches easily to tractors, loaders, or telehandlers, helping you keep the feed area tidy and the job quick to finish.



FEATURES

- A simple sliding beam action will enable the pusher to be extended for different passage widths
- Suitable for feed passages of 8 to 15ft wide
- Robust main frame designed so loader brackets can be easily mounted.
- The tyres are angled so that the outside edges are in contact with feed passage first to enable the correct direction of rotation and feed movement.
- The tyres are mounted on axles to provide years of trouble free operation.
- Supplied with super single tyres that can be easily replaced and are available free from most commercial tyre dealers
- Available as single arm Silage Pusher.

- A tractor bracket is available to enable connection via the 3 point linkage or to an A frame
- Pallet fork bracket available sold seperately
- Telescopic/loader brackets sold seperately

SPECIFICATIONS

Twin Wheel - Bracket Mounted

Code	66200
Height	1000mm
Length	1160mm
Min Width	2440mm
Max Width	4260mm
Weight	300kg
Price	Call 0113 487 7511

Twin Wheel - 3 Point Linkage

Code	66210
Height	1000mm
Length	1160mm
Min Width	2440mm
Max Width	4260mm
Weight	300kg
Price	Call 0113 487 7511

Single Wheel - Bracket Mounted

Code	66220
Height	1000mm
Length	1160mm
Min Width	2020mm
Max Width	2620mm
Weight	225kg
Price	Call 0113 487 7511

Single Wheel - 3 Point Linkage

Code	66230
Height	1000mm
Length	1160mm

Min Width	2020mm
Max Width	2620mm
Weight	225kg
Price	Call 0113 487 7511

OPTIONS

Currently there are no options added to this product.

TESTIMONIALS

Currently there are no testimonials added to this product.